

The Best & Last Roof Coating You'll Ever Use!



- The Last Roof Coating You'll Ever Need
- Withstands Permanent Ponding Water
- Ideal for Flat or Sloped Roofs



GacoRoof is Excellent for:

- Aged Asphalt*
- Aged EPDM*
- Aged TPO/CPA*
- Cap Sheet
- Composite
- Concrete
- Fiberglass
- Metal
- Modified Bitumen
- Smooth Built-Up
- Torchdown
- Sprayed Polyurethane Foam
- Most Existing Coatings
- Low-Pitched Roofs
- Flat Roofs
- Mobile Homes

*Not for use on 3-tab asphalt or architectural shingles.

*May require GacoFlex E5320 2-Part Epoxy Primer/Filler. Verify adhesion with AdhesionTestKit.

White GR1600	Gray GR1628	Green GR1626
Light Tan GR1670	Rustic GR1671	Medium Blue GR1672
Black GR1673	Brown GR1674	Red GR1675

Note: Colors shown are printed representations of product color. Actual color may vary slightly due to surface texture, application technique and lighting conditions.

Turn over to compare for yourself...

Gaco[™]

Compare for Yourself



	GacoRoof	Brand X
Warranty	Limited 50-Year	5-10 Years
Can be applied between 32°F - 120°F	YES	NO
Withstands Permanent Ponding Water	YES	NO
Primer/ Basecoat Required	NO	YES
Re-coating Required	NO	YES

- 2 coat application of same product
Brand X requires multiple products
- Withstands permanent ponding water
Brand X is 48 hours only
- Temperature application range
32°F - 120°F
Brand X is 50°F - 90°F
- 1-12 hour cure time, dry to the touch
Brand X is 24-48 hours
- 1 gallon = 100 sq. ft. per coat
Brand X is 1.5 gallons
- Can be used on flat roofs
Brand X requires 1/4" slope
- Can be rained on after 2 hours
Brand X requires no rain, dew or fog within 24-48 hours

- Permanently flexible
Brand X becomes brittle and begins to degrade over time
- Recoat can be done after cure time
Brand X may require 24 hours before re-coat
- Silicone Roof Coating
Brand X sells all acrylic roof coatings
- Ponding waterproof
Brand X is ponding water resistant
- 50 year warranty
Brand X 5-10 year warranty
- No polyester mat between coats
Brand X requires polyester mat
- UV resistant
Brand X loses mil thickness due to UV exposure
- 22 mil system
Brand X is 48-60 mil

For more information call 800.331.0196 or reach out to your GacoFlex Local Area Manager at [Gaco.com/representatives](https://www.gaco.com/representatives).